

Rack Mount Amplifier S120L



The Chevin S120L is designed for meeting every standard for distributed sound systems with isolated 50V, 70V and 100V outputs. Its passive cooling providing silent operation. Powder coated steel face plates and heavy-duty steel chassis reflect the manufacturing quality within. It carries the CE approval for world-wide use.

POWER 120 Watt



OUTPUTS 50 Volt 70 Volt 100 Volt



CONVECTION Cooling



CONNECTORS Inputs XLR –balanced RCA



Output Phoenix covered



AUTOMATIC PROTECTION

Technical specification

Power output (1kHz at 1.0%THD)		120 W
Input sensitivity	1V	
Input impedance	20 kΩ	Balanced
THD	1 kHz	< 0.07 %
Frequency response	- 3 dB	20Hz - 20kHz
S/N Ratio	> 95 dB (> 98 dB "A")	
Output [V]	50 / 70 / 100	

Features:

- automatic signal limiter
- thermal protection & automatic idling circuitry to insure stability and reliability against over-current and overheating, thermal protection circuitry is provided
- convection cooling (without fan)

Inputs:

- balanced XLR male + female
- unbalanced RCA left + right

Indicators:

- ON green LED
- SIGNAL green LED
- PEAK red LED

Controls:

- Power switch On / Off
- volume level adjustment control

Power Requirements	AC ~ 230V / 120V	50 / 60Hz
Rack	1U	
Dimensions	485 x 44 x 295 mm	
Weight	6 kg	

